

MORSØ - UPM

Frame Assembling Machine

Manually operated by a hydraulic foot-pedal

Bench Model

Ideal machine for low volume production.

- ▼ Manually operated
- ▼ No compressor needed
- ▼ Exact 45° assembling
- ▼ No noise

MORSØ-UPM is a manually operated bench model activated by a single pressure on a hydraulic foot pedal. The **MORSØ-UPM** is ideal for the small shop with a limited space.

The **MORSØ-UPM** can be placed almost everywhere, and is operated without use of compressor or electricity.

Solid machine which has been built to last.



MORSØ - UPM

Frame Assembling Machine

Manually operated by a hydraulic foot pedal

TECHNICAL DATA

SUBJECT	SPECIFICATION
Wedge sizes	5, 7, 10 and 12 mm
Thickness of moulding, min.	6 mm (¼")
Thickness of moulding, max.	55 mm (2")
Width of moulding, min.	6 mm (¼")
Width of moulding, max.	105 mm (4")
Distance between wedges, max	85 mm (3")
Height, working bench	176 mm (7")
Machine dimension:	
Length x width x height	335x240x420 mm (13x9½x16½")
Weight	25 kilos (55 lbs)

The main features of the MORSØ UP-M are:

- bench model – can be placed almost everywhere
- manually operated by single pressure on a hydraulic foot pedal
- no compressor or electricity needed
- noiseless operation
- exact 45° assembling
- built to last

MORSØ UPM is delivered with: ACCESSORIES:

- | | |
|---|--|
| <ul style="list-style-type: none"> • Two adjustable stops for min. and max. wedge position. • Single pressure pad for plain mouldings • Two double pressure pads for mouldings with different profiles • Adjustable fences - 90°, 60°, and 30° for rectangular, hexagonal and octagonal frames • Two refillable solid-steel cartridges for 7 and 10 mm wedges, respectively • Hydraulic foot pedal • One box of 7 mm wedges (5000 pcs) • One box of 10 mm wedges (2700 pcs) | <ul style="list-style-type: none"> • 5 mm steel cartridge • 12 mm steel cartridge • 5 mm wedges – 1 box 5000 pcs • 12 mm wedges – 1 box 5400 pcs • Stand for the machine Height: 840 mm |
|---|--|


Double pressure pads:

One for mouldings with standard profile and one for mouldings with reversed profile.



Padded with synthetic fibres ensuring no marks at all are left on the frame.

Flat pressure pad for plain mouldings.

Padded with synthetic fibres ensuring no marks at all are left on the frame.


Solid steel cartridges:

5, 7, 10, and 12 mm.


MODELS

MORSØ - UPH

MORSØ - UPA

MORSØ - UPAKS

DISTRIBUTOR
